




Switches


Standard CTI Switches




CTI Pushbutton Switches



Circuit Diagram



Panel Cutout Dimensions





CTI Part # **32-P-A91113-01** SPDT - mom (DC w/leads)


Technical Data

Cycles: 10,000,000
 Current Rating: 5 amps@ 30vDC
 Temperature Range: -40°C to +85° @ Rated Current
 Internal Seals: N/A


Spring Rate: 6.9 lbs
 Environmental Protection: IP40, IP67
 Wire Leads: 4"
 Terminals: Male Bullet 22-16, 0.156



Circuit Diagram



Panel Cutout Dimensions




CTI Part # **32-P-040004-01** SPDT - mom (DC w/S/leads)


Technical Data

Cycles: 10,000,000
 Current Rating: 5 amps@ 30vDC
 Temperature Range: -40°C to +85° @ Rated Current
 Internal Seals: N/A


Spring Rate: 6.9 lbs
 Environmental Protection: IP40, IP67
 Wire Leads: 4"
 Terminals: Male Amp



Circuit Diagram



Panel Cutout Dimensions



CTI Part # **32-P-970147-01** SPDT - mom (RS)

Technical Data

Cycles: 10,000,000
 Current Rating: 5 amps@ 120vAC, 30vDC
 Temperature Range: -40°C to +85° @ Rated Current
 Internal Seals: N/A

Spring Rate: 6.9 lbs
 Environmental Protection: IP40, IP67
 Wire Leads: None
 Terminals: None

www.cyber-tech.net

1-800-621-8754

