



# Switches


### **Standard CTI Switches**

#### CTI Pushbutton Switches










CTI Part # 32-P-970046-01 SPDT - mom (RS DC w/leads)

Technical Data


Cycles: 10,000,000
Current Rating: 5 amps@30vDC
Temperature Range: -40°C to +85° @ Rated Current
Internal Seals: N/A

Spring Rate: 6.9 lbs
Environmental Protection: IP40, IP67
Wire Leads: 4"
Terminals: Male Amp










#### Panel Cutout Dimensions




CTI Part # 32-P-11511-02 SPDT - mom (S10A)


Technical Data


Cycles: 10,000,000
Current Rating: 10 amps@ 120vAC, 30vDC
Temperature Range: 40°C to +85° @ Rated Current
Internal Seals: N/A

Spring Rate: 6.9 lbs
Environmental Protection: IP40, IP67
Wire Leads: N/A
Terminals: N/A









CTI Part # 32-P-A11511-01 SPDT - mom (S10A DC w/leads)

Technical Data

## www.cyber-tech.net

1-800-621-8754

Cycles: 10,000,000
Current Rating: 10 amps@ 30vDC
Temperature Range: 40°C to +85° @ Rated Current
Internal Seals: N/A

Spring Rate: 6.9 lbs Environmental Protection: IP40, IP67 Wire Leads: 4" Terminals: Bullet M/F 22-16, 0.156

"a commitment to intergrated engineering & design"

Document Date: 06-01-2005